

Smart Infrastructure and Machine Learning Integration for Advanced Additive and Hybrid Manufacturing

Md Rehan Uddin ^{1*}

¹ Master of Business Administration, Manipal University, Jaipur, India
E-mail: rehanlaskar084@gmail.com

ARTICLE INFO

Keywords:


Smart Manufacturing;
Machine Learning; Additive
Manufacturing; Digital
Twins; Edge Computing

Vol.01, No.05, 2026

<https://doi.org/10.5281/zenodo.23159745>

Copyright © 2026 by author(s) and Scientific Research Publishing Inc. This work is licensed under the Creative Commons Attribution International License (CCBY4.0).

<http://creativecommons.org/licenses/by/4.0/>



ABSTRACT

The integration of smart infrastructure and machine learning (ML) is transforming additive and hybrid manufacturing by enabling interconnected, data driven, and adaptive production systems. This study examines the integration of digital twins, artificial intelligence, edge computing, cloud analytics, Industrial Internet of Things technologies, and interoperable automation architectures across additive manufacturing workflows. Particular attention is given to ML methods for process optimization, material and property prediction, real time monitoring, anomaly detection, defect classification, predictive maintenance, and closed loop process control. Digital twins are considered as dynamic representations that combine physical models, live sensor information, and data driven prediction to support continuous process adaptation. The study also evaluates the roles of federated learning, physics informed modeling, transfer learning, and reinforcement learning in improving generalization and intelligent control across heterogeneous manufacturing environments. Applications in aerospace, biomedical engineering, automotive production, consumer products, and infrastructure demonstrate the potential of intelligent additive manufacturing to improve quality, efficiency, customization, reliability, and resource utilization. However, practical deployment remains constrained by data heterogeneity, model transferability, computational requirements, communication latency, interoperability, cybersecurity, data governance, and regulatory compliance. Edge cloud architectures provide a potential solution by combining low latency local processing with scalable cloud based analytics and model management. Overall, intelligent additive and hybrid manufacturing requires coordinated development of sensing, computation, digital modeling, machine learning, and secure data infrastructure. Continued progress in standardized datasets, interoperable platforms, validated digital twins, and physics informed ML can support the transition from experimental demonstrations toward scalable, reliable, and increasingly autonomous industrial manufacturing systems.

Introduction

Smart infrastructure and machine learning integration are shaping an intelligent production paradigm for additive manufacturing (AM) and related hybrid processes. This approach combines software-defined automation, edge and cloud analytics, digital twins, and cross vendor data interoperability to transform fragmented manufacturing workflows into cohesive, end to end process chains [1]. Real time data access, cause and effect learning, and autonomous process adjustment can support improved control of critical manufacturing outcomes, including melt pool behavior, porosity, density, distortion, surface quality, and mechanical and microstructural properties. Energy input represents an important linking variable between process parameters and final part performance. The integration of AM with smart manufacturing technologies places industrial artificial intelligence, machine learning, the Industrial Internet of Things, and advanced sensing at the center of production optimization [2]. Digital twins, federated learning, physics informed machine learning, and edge computing can facilitate predictive maintenance, in process quality control, anomaly detection, and

scalable optimization across machines and production sites. Such systems can continuously interpret manufacturing data and support rapid responses to process deviations, reducing dependence on isolated machine level operations. High temperature and enclosed manufacturing environments create challenges related to image quality, lighting, optical geometry, and surface characteristics [3]. Image preprocessing techniques such as contrast enhancement can improve segmentation and defect identification, while ground truth data and model predictions can be used to evaluate the performance of AI based inspection systems. Three dimensional imaging can further support automated defect localization and characterization. Digital image correlation and engineered surface patterns also provide opportunities for measuring deformation and surface behavior during manufacturing [4]. The technological diversity of AM requires careful consideration of process parameters and materials. Polymer, ceramic, and metallic manufacturing processes involve variables such as layer height, wall thickness, infill, nozzle and bed temperature, printing speed, and material composition. These parameters directly influence surface roughness, dimensional accuracy, tensile strength, and other final part properties. Machine learning can assist in identifying relationships between process conditions and manufacturing outcomes, allowing parameters to be optimized according to specific performance requirements [5]. Despite these opportunities, production scale implementation remains constrained by end to end latency, heterogeneous control systems, incompatible data formats, computational demands, data governance, cybersecurity, and regulatory requirements. Standardized datasets, interoperable platforms, open innovation environments, and shared manufacturing infrastructures are therefore important for advancing the field [6]. Collaboration between industry and academia can support benchmarking, knowledge exchange, and development of engineers with combined expertise in manufacturing and artificial intelligence. Overall, the integration of smart infrastructure, machine learning, sensing, and digital twins provides a pathway toward more adaptive, connected, and autonomous AM and hybrid manufacturing systems. Continued development of interoperable data architectures, reliable AI based monitoring, closed loop control, and scalable computational infrastructure will be essential for translating these technologies from individual demonstrations into dependable industrial production environments [7].

1. Architecture, and Smart Infrastructure Components

A digital twin in additive manufacturing (AM) is a virtual representation of a physical manufacturing system that maintains a bidirectional, real time connection with the production process. Unlike static simulations or standalone machine learning models, it continuously updates its state using live sensor data and can support predictive analysis and feedback actions. In composite 3D printing, a digital twin can represent the printing process and potentially the evolving part, integrating real time printer data with predictive models to anticipate process outcomes and deviations [8]. Machine learning integration increasingly emphasizes closed loop control, shifting manufacturing from reactive responses toward predictive operation (Table 1). Edge AI enables computational tasks to be performed close to the printer, reducing communication latency and supporting real time process adaptation. However, model generalization remains a major challenge because differences in machines, materials, process conditions, and equipment configurations can significantly affect model performance [9]. Transfer learning, domain adaptation, physics informed learning, and cross validation can improve transferability, although substantial differences between manufacturing platforms may still limit generalization. Smart infrastructure provides the interconnected foundation required for these capabilities (Figure 1). The Internet of Things (IoT) and Industrial Internet of Things (IIoT) connect machines, sensors, equipment, and production assets to facilitate continuous data collection and exchange [10]. Edge computing processes information close to its source, reducing latency and enabling distributed analytics. Time

sensitive networking and machine to machine communication further support reliable, low latency information exchange for adaptive manufacturing. Collectively, these components establish an integrated architecture capable of supporting efficient, adaptive, resilient, and increasingly autonomous AM and hybrid manufacturing systems [11].




Figure 1. Smart Manufacturing for High-Performance Materials [47]

Table 1. Smart infrastructure and machine learning technologies in additive and hybrid manufacturing

Technology / Approach	Main Function	Manufacturing Application	Key Benefit	Reference
Digital twins	Creates a dynamic virtual representation of the physical manufacturing system using live process data	Process prediction, monitoring, optimization, and feedback control	Supports continuous process adaptation and predictive decision making	[8], [31], [34]
Machine learning	Learns relationships between process parameters, materials, sensor data, and manufacturing outcomes	Process optimization, property prediction, defect detection, and quality assessment	Enables data driven prediction and optimization	[9], [12], [35]
Deep learning	Processes high dimensional images, thermal fields, and multimodal sensor data	Defect detection, image analysis, and real time monitoring	Effective for complex manufacturing data	[13], [36]
Physics informed ML	Integrates physical relationships with data driven learning	Process prediction, material behavior and generalizable optimization	Can improve physical consistency and reduce dependence on large datasets	[37], [38]

2. Machine Learning Methods, Applications, Data, Training, and Evaluation

Artificial intelligence (AI) and machine learning (ML) are increasingly being applied to material development, process optimization, quality monitoring, and defect detection in gel, polymer, and composite additive manufacturing (AM). Decision trees, random forests, support vector machines, neural networks, deep learning, and Bayesian optimization can predict rheological behavior, print fidelity, mechanical properties, and other outcomes from formulation and processing data [12]. Interpretable ML can also clarify how material additives and processing variables influence print performance, supporting faster exploration of formulation spaces and reducing experimental requirements. The selection of an ML method depends on data availability, process complexity, and the required balance between accuracy and interpretability [13]. Supervised models such as random forests, support vector regression, and shallow neural networks can perform effectively when datasets are relatively small and features are well defined. Deep learning is more suitable for high dimensional inputs such as images, thermal fields, and continuous sensor streams, although greater computational and data requirements are introduced. Reinforcement learning offers potential for adaptive process control but is generally more computationally demanding and is often implemented through simulation assisted or hybrid frameworks [14]. Process parameter optimization represents an important application of ML in AM. Evolutionary algorithms and Bayesian optimization can identify printing conditions that improve strength, reduce warping, minimize porosity, and enhance dimensional accuracy. Multi objective optimization can simultaneously consider several performance requirements while surrogate models reduce the number of physical experiments needed. Data from successful and defective prints can also be incorporated into continuous learning systems to identify recurring defect causes and guide subsequent process adjustments. When combined with digital twins, these approaches can support predictive rather than reactive process control. Real time monitoring provides another major application area [15]. High speed imaging, three dimensional sensing, and ultrasonic measurements can be used to identify surface and internal defects such as voids, delamination, and other structural abnormalities. ML models can analyze time domain, frequency domain, and time frequency features from ultrasonic signals, while computer vision models can detect small surface defects in printed components. ML can also predict mechanical properties such as flexural strength from material composition and processing conditions, providing a virtual assessment framework for selecting suitable manufacturing parameters [16].

3. Real Time Constraints, Deployment Feasibility and Compliance

Real time deployment of digital twins and edge enabled architectures in additive and hybrid manufacturing is constrained by system integration, scalability, computational requirements, and latency. Integrating digital twins with existing manufacturing equipment can require substantial investment in software, hardware, infrastructure, and technical expertise [17]. Scalability is also challenging because systems must accommodate increasing numbers of sensors, machines, and production processes without compromising performance. Computationally intensive technologies such as augmented reality and adaptive online simulation can further limit deployment in resource constrained environments. Real time monitoring and closed loop control require rapid data processing and low latency decision making so that process deviations can be detected and corrected during manufacturing [18]. Predictive maintenance and remote troubleshooting through Industrial Internet of Things platforms can improve equipment availability, but they also increase data processing and communication requirements. A balance between local processing and cloud based resources is therefore required. Edge computing can handle time critical operations locally, while cloud infrastructure can provide model management, storage, and large scale analytics. Hybrid edge cloud architectures provide a practical

approach for heterogeneous manufacturing environments [19]. High volume and latency sensitive tasks such as defect detection can be performed on local edge devices, while computationally intensive analytics and model lifecycle management can be transferred to cloud platforms when network conditions permit. Such architectures can also support data privacy and regulatory requirements by keeping sensitive information within local infrastructure. System performance remains dependent on factors including input data size, device capabilities, model complexity, and communication conditions [20]. Deployment across complete manufacturing workflows introduces additional challenges because equipment from different vendors may use incompatible control systems, communication protocols, and data formats. An intelligent AM cell therefore requires interoperable interfaces and coordinated data exchange among printers, sensors, robotic systems, post processing equipment, and information systems (Figure 2). Standardized data models and communication interfaces are important for enabling scalable digital twin ecosystems and continuous end to end process adaptation [21]. Compliance requires trustworthy data, transparent data management, traceability, and auditable manufacturing records. In process measurements can be used to evaluate part performance, demonstrate conformity with specifications, and support certification. Secure platforms are also required to protect manufacturing data and intellectual property as connectivity increases. Cybersecurity therefore forms an integral part of deployment feasibility, particularly where manufacturing systems are connected across machines, facilities, and cloud environments [22]. Collectively, real time computing, interoperable architectures, continuous monitoring, secure data management, and adaptive control provide the foundation for reliable and compliant intelligent manufacturing systems.




Figure 2. Additive Manufacturing Modification by Artificial Intelligence [48]

4. Implementation and Deployment

Implementation of next generation smart infrastructure increasingly emphasizes modular production, factory based manufacturing, and software defined automation. Factory based approaches demonstrate how controlled production environments can integrate design, manufacturing, and assembly while reducing delays and improving coordination between off site fabrication and on site construction [23]. Modular components can be manufactured under controlled conditions, transported to the required location, and assembled efficiently, illustrating the broader potential of standardized and coordinated production systems. In additive and hybrid manufacturing, software defined automation platforms provide a central mechanism for coordinating diverse production assets (Table 2). These platforms can connect 3D printers, post processing equipment, robotics, inspection systems, sensors, safety controllers,

and factory information systems [24]. By coordinating these components through a unified infrastructure, production activities can be sequenced in real time while data are collected continuously for machine learning training, inference, prediction, and process control. This architecture supports the development of cohesive production chains rather than isolated machine operations. Deployment also requires AM to be treated as an integrated component of the broader manufacturing process. Open and extensible architectures can coordinate printers, robots, factory equipment, and information technology systems while synchronizing production data across the complete workflow [25]. Such coordination is necessary for reducing downtime, managing bottlenecks, maintaining compliance, and supporting AI based optimization. Without effective orchestration, fragmented data and disconnected production stages can limit scalability and reduce the effectiveness of intelligent manufacturing systems [26]. Overall, effective implementation depends on modular production structures, interoperable software architectures, coordinated factory assets, reliable data infrastructures, and distributed computing capabilities. The integration of edge computing, digital twins, and AI based automation provides a practical foundation for developing scalable AM and hybrid manufacturing systems capable of continuous monitoring, prediction, and closed loop process adjustment.

Table 2. Applications, benefits, and challenges of intelligent additive and hybrid manufacturing

Application Area	Smart Manufacturing Application	Expected Manufacturing Outcome	Major Challenge	Reference
Aerospace and defense	AI based process optimization, topology optimization, in situ monitoring, and digital twins	Lightweight, high strength components, improved reliability, traceability, and certification	Strict quality, reliability, and certification requirements	[27], [28], [43]
Biomedical engineering	AI assisted material selection, patient specific design, lattice optimization, and digital workflows	Customized implants and prosthetics with controlled mechanical properties	Biocompatibility, patient specific requirements, and quality assurance	[29]
Automotive manufacturing	Intelligent composite AM, process monitoring, predictive maintenance, and automated optimization	Improved production efficiency, material utilization, customization, and rapid prototyping	Cost, throughput, equipment integration, and scalability	[30], [25]
Consumer products	AI assisted design, customized AM, real time monitoring, and process correction	Rapid production and customized components	Balancing production speed, cost, and quality	[30]

5. Case Studies and Use Cases

Intelligent additive manufacturing (AM) is being applied across aerospace, biomedical, automotive, consumer, and infrastructure sectors, where artificial intelligence (AI), digital twins, real

time monitoring, and automated optimization are used to improve performance, reliability, and manufacturing efficiency [27]. In aerospace and defense, intelligent composite 3D printing is used to develop lightweight components with high strength to weight ratios. AI based optimization can guide the printing of continuous fiber reinforced thermoplastics such as PEEK and PEI by selecting suitable process strategies and print paths. Topology optimization can further reduce unnecessary material while maintaining structural performance. In situ monitoring provides continuous assessment of deposited layers, allowing defects to be detected during manufacturing and enabling corrective action or rejection when required [28]. Digital twins and closed loop monitoring can additionally support design verification, process control, traceability, and certification of high value aerospace components. Biomedical engineering places greater emphasis on biocompatibility, biomechanical compatibility, and patient specific design. AI can assist in material selection and optimization of composite formulations for implants and prosthetics. Patient imaging data can be integrated into digital design workflows to develop customized structures such as cranial and intervertebral implants [29]. Internal lattice architectures can be optimized according to patient specific mechanical requirements while controlling weight and material usage. Real time manufacturing monitoring can provide additional quality assurance, creating a connected workflow from medical imaging and AI assisted design to fabrication and inspection. Automotive and consumer applications focus on balancing performance, production cost, material efficiency, and manufacturing speed [30]. Intelligent composite AM can support low volume production, customized components, and rapid prototyping. Real time monitoring and process correction are particularly useful for large components because defects can be identified during fabrication rather than after completion. Across these applications, iterative workflows combining AI based optimization, in situ sensing, digital twins, and physics based models are supporting the transition toward production scale intelligent AM. Model selection remains dependent on the characteristics of the manufacturing process and available data [31]. Physics based models can provide strong predictive capability where material behavior is well characterized, while data driven models can capture complex relationships from large experimental datasets. Hybrid approaches therefore provide a means of combining physical knowledge with machine learning while improving adaptability across heterogeneous manufacturing systems [32].

6. Discussion

The integration of smart infrastructure, machine learning, digital twins, and additive manufacturing represents a significant transition from isolated fabrication systems toward interconnected and adaptive production environments. The findings synthesized across the preceding sections indicate that intelligent additive and hybrid manufacturing should not be understood simply as the addition of artificial intelligence to existing printers. Rather, it represents an architectural transformation in which machines, sensors, software, computational resources, digital models, and production data are connected within a continuous decision making framework [33]. This transformation is particularly important because additive manufacturing is inherently data intensive and highly sensitive to interactions among material properties, process parameters, environmental conditions, machine characteristics, and geometric complexity. A central finding is the importance of digital twins as an organizing component of intelligent manufacturing. A true digital twin differs from a conventional simulation or machine learning surrogate because it maintains a continuous relationship with its physical counterpart [34]. Sensor measurements can update the virtual representation, while predictions generated by the digital model can support decisions affecting the physical process. Machine learning provides another major component of this transformation. Different algorithms offer different advantages depending on the nature of the manufacturing data and the intended application. Random forests, support

vector machines, shallow neural networks, and related supervised approaches can perform effectively when datasets are relatively limited and process variables are clearly defined [35]. Deep learning becomes more appropriate for complex image, thermal, and multimodal datasets, although greater computational requirements and reduced interpretability can be introduced. Reinforcement learning offers a pathway toward adaptive control because actions can be selected according to changing process states, but computational demands and the requirement for reliable training environments remain important limitations [36]. Therefore, algorithm selection should be determined by process characteristics, data availability, computational resources, and the required degree of interpretability rather than by the assumption that a single AI method is universally superior. The analysis also demonstrates the importance of combining data driven methods with physical knowledge. Purely empirical machine learning can perform well within the conditions represented by its training data but may become unreliable when material, machine, geometry, or environmental conditions change [37]. Physics informed and hybrid models can constrain predictions according to known thermomechanical relationships, reducing dependence on large experimental datasets and potentially improving generalization. This is particularly relevant in additive manufacturing, where changes in energy input, cooling behavior, material rheology, deposition rate, and geometry can alter the resulting part properties. Hybrid modeling therefore provides a means of combining the flexibility of machine learning with established physical relationships [38]. Model generalization remains one of the most important unresolved issues. A model developed for one printer and material combination cannot automatically be assumed to perform equally well on another system. Differences in machine architecture, sensor configuration, feedstock characteristics, environmental conditions, and process control can alter the relationship between input variables and manufacturing outcomes. Transfer learning and domain adaptation provide possible solutions, particularly when only a limited amount of new training data is available [39]. Nevertheless, substantial differences between manufacturing platforms may restrict the effectiveness of these approaches. Standardized datasets, benchmark protocols, and common evaluation procedures are therefore necessary for meaningful comparison and reliable deployment. The discussion of smart infrastructure further demonstrates that intelligent AM depends on interoperability across the entire production environment. Printers cannot operate as isolated intelligent units if post processing, robotics, inspection, safety systems, enterprise software, and supply chain operations remain disconnected [40]. Software defined automation can provide an orchestration layer that coordinates these heterogeneous assets and establishes continuous data flow across the production chain. Open interfaces and standardized data models are particularly important because vendor specific systems and incompatible data formats can create information silos. Without interoperability, the benefits of machine learning and digital twins remain restricted to individual machines or isolated production stages [41]. Data quality is equally important. Machine learning systems depend on representative and accurately labeled data, while digital twins require reliable sensor information to maintain meaningful representations of physical processes. The discussed anomaly detection framework illustrates the importance of expert annotation, appropriate dataset partitioning, and independent evaluation. Defect masks, machine element labels, and part segmentation provide different forms of ground truth depending on the analytical task. Metrics such as AUROC, AUPRO, F1 score, and intersection over union allow performance to be evaluated from complementary perspectives [42]. Such practices are important because high apparent model performance can result from data leakage, insufficiently diverse datasets, or inconsistent annotation practices. The applications discussed across aerospace, biomedical, automotive, consumer, and infrastructure sectors demonstrate the broad potential of intelligent AM while also revealing differences in operational requirements. Aerospace applications place strong

emphasis on lightweighting, structural reliability, traceability, and certification [43]. Biomedical applications require patient specific design, biocompatibility, and controlled mechanical properties. Automotive and consumer applications place greater emphasis on cost, throughput, customization, and material efficiency. Infrastructure applications require long term monitoring, structural assessment, and integration with broader asset management systems [44]. These differences indicate that intelligent manufacturing architectures should remain modular and adaptable rather than being designed around a single application domain. Quality assurance represents one of the strongest practical applications of machine learning in AM. Conventional inspection frequently occurs after fabrication, meaning that defects may only be discovered after significant material, energy, and production time have already been invested. In situ monitoring changes this relationship by allowing defects to be identified while fabrication is underway. Vision systems can detect surface abnormalities, while ultrasonic and other sensing approaches can provide information about subsurface conditions [45]. When these systems are integrated with closed loop control, detected deviations can potentially trigger changes in process parameters before the defect propagates. Overall, the evidence indicates that intelligent additive and hybrid manufacturing is best understood as an integrated cyber physical production ecosystem. Machine learning supplies predictive and analytical capabilities, digital twins provide dynamic representations of physical processes, edge computing supports low latency decisions, cloud systems provide scalable computational resources, and interoperable infrastructure connects machines and information systems [46]. The effectiveness of this ecosystem depends on the interaction among these components rather than on the performance of any single technology.

7. Conclusion

Smart infrastructure and machine learning are transforming additive and hybrid manufacturing by integrating digital twins, intelligent sensing, edge computing, cloud analytics, and automated process control. These technologies enable real time monitoring, predictive maintenance, defect detection, process optimization, and adaptive manufacturing across diverse industrial applications. However, widespread deployment remains constrained by interoperability, latency, data quality, model generalization, computational requirements, cybersecurity, and regulatory compliance. Future progress will depend on standardized data architectures, physics informed machine learning, reliable multimodal sensing, scalable edge cloud systems, and validated digital twins. Their integration can support more efficient, reliable, adaptive, sustainable, and increasingly autonomous manufacturing ecosystems.

Author Contributions

M.R.U. Conceptualization, literature search and review, data curation, analysis and interpretation of the literature, writing original draft preparation, writing review and editing, and final approval of the manuscript.

References

- [1] B. Baufeld, "Wire electron beam additive manufacturing of copper," *J. Phys. Conf. Ser.*, vol. 2443, no. 1, p. 012001, 2023, doi: 10.1088/1742-6596/2443/1/012001.
- [2] M. A. Hossain, S. C. Barman, and S. M. T. Islam, "Additive manufacturing of lightweight, fire-resistant alloys for automotive and aerospace applications," *J. Mech. Civil Ind. Eng.*, vol. 7, no. 3, pp. 06–16, 2026, doi: 10.32996/jmcie.2026.7.3.2.
- [3] H. K. Celik, A. Elham, M. A. Erbil, A. E. W. Rennie, and I. Akinci, "A decade of design for additive manufacturing research: A bibliometric analysis (2014-2024)," *Rapid Prototyp. J.*, ahead-of-print, 2025, doi: 10.1108/RPJ-02-2025-0086.

- [4] S. Chattopadhyay, S. D. Mahapatra, and N. K. Mandal, "Advancements and challenges in additive manufacturing: A comprehensive review," *Eng. Res. Express*, vol. 6, no. 1, p. 012505, 2024, doi: 10.1088/2631-8695/ad30b1.
- [5] F. Chénier, G. Parent, M. Leblanc, C. Bélaïse, and M. Andrieux, "Using a quantitative assessment of propulsion biomechanics in wheelchair racing to guide the design of personalized gloves: A case study," *arXiv*, 2023, doi: 10.1080/10255842.2024.2311324.
- [6] W. Du, Q. Bai, and B. Zhang, "A novel method for additive/subtractive hybrid manufacturing of metallic parts," *Procedia Manuf.*, vol. 5, pp. 1018–1030, 2016, doi: 10.1016/j.promfg.2016.08.067.
- [7] J. Duflou and K. Kellens, "Cleaner production," in *CIRP Encyclopedia of Production Engineering*, Berlin/Heidelberg, Germany: Springer, 2016, pp. 1–4, doi: 10.1007/978-3-642-35950-7_6635-3.
- [8] J. M. Flynn, A. Shokrani, S. T. Newman, and V. Dhokia, "Hybrid additive and subtractive machine tools-Research and industrial developments," *Int. J. Mach. Tools Manuf.*, vol. 101, pp. 79–101, 2016, doi: 10.1016/j.ijmachtools.2015.11.007.
- [9] M. A. Hossain, M. A. A. Bhuiyan, A. Rahman, and D. W. Hasan, "Integration of artificial intelligence for real-time monitoring and process control in metal additive manufacturing systems," *J. Mech. Civil Ind. Eng.*, vol. 5, no. 3, pp. 08–28, 2024, doi: 10.32996/jmcie.2024.5.3.2.
- [10] B. Freitas *et al.*, "A review of hybrid manufacturing: Integrating subtractive and additive manufacturing," *Materials*, vol. 18, no. 18, p. 4249, 2025, doi: 10.3390/ma18184249.
- [11] A. Jakimiuk, A. Skwira, Z. Wróbel, and Z. Wróbel, "3D-printed patient-specific implants made of polylactide (PLDLLA) and tricalcium phosphate TCP) for corrective osteotomies of the distal radius," *3D Print. Med.*, vol. 10, p. 42, 2024, doi: 10.1186/s41205-024-00240-z.
- [12] H. Jayawardane, I. J. Davies, J. R. Gamage, M. John, and W. K. Biswas, "Sustainability perspectives-A review of additive and subtractive manufacturing," *Sustain. Manuf. Serv. Econ.*, vol. 2, p. 100015, 2023, doi: 10.1016/j.smse.2023.100015.
- [13] A. Jiménez *et al.*, "Powder-based laser hybrid additive manufacturing of metals: A review," *Int. J. Adv. Manuf. Technol.*, vol. 114, pp. 63–96, 2021, doi: 10.1007/s00170-021-06855-4.
- [14] S. Jung, L. B. Kara, Z. Nie, T. W. Simpson, and K. S. Whitefoot, "Is additive manufacturing an environmentally and economically preferred alternative for mass production?," *Environ. Sci. Technol.*, vol. 57, no. 17, pp. 6373–6386, 2023, doi: 10.1021/acs.est.2c04927.
- [15] S. Kapil, A. S. Rajput, and R. Sarma, "Hybridization in wire arc additive manufacturing," *Front. Mech. Eng.*, vol. 8, p. 981846, 2022, doi: 10.3389/fmech.2022.981846.
- [16] M. A. Hossain, W. Pi, S. M. T. Islam, and M. I. Lide, "Smart manufacturing framework for real-time process monitoring, predictive maintenance, and quality control in advanced mechanical production systems," *J. Mech. Civil Ind. Eng.*, vol. 2, no. 1, pp. 11–24, 2021, doi: 10.32996/jmcie.2021.2.1.3.
- [17] K. P. Karunakaran, S. Suryakumar, V. Pushpa, and S. Akula, "Low cost integration of additive and subtractive processes for hybrid layered manufacturing," *Robot. Comput.-Integr. Manuf.*, vol. 26, no. 5, pp. 490–499, 2010, doi: 10.1016/j.rcim.2010.03.008.
- [18] U. Khan *et al.*, "A comprehensive survey on deep learning-based predictive maintenance," *ACM Trans. Embed. Comput. Syst.*, vol. 25, no. 1, pp. 1–43, 2026, doi: 10.1145/3732287.
- [19] A. A. Krimpenis and D. M. Iordanidis, "Design and analysis of a desktop multi-axis hybrid milling-filament extrusion CNC machine tool for non-metallic materials," *Machines*, vol. 11, no. 6, p. 637, 2023, doi: 10.3390/machines11060637.

- [20] D. Lalegani *et al.*, "A review on additive/subtractive hybrid manufacturing of directed energy deposition (DED) process," *Adv. Powder Mater.*, vol. 1, no. 2, p. 100054, 2022, doi: 10.1016/j.apmate.2022.100054.
- [21] B. Lauwers, F. Klocke, A. Klink, A. E. Tekkaya, R. Neugebauer, and D. McIntosh, "Hybrid processes in manufacturing," *CIRP Ann.-Manuf. Technol.*, vol. 63, no. 2, pp. 561–583, 2014, doi: 10.1016/j.cirp.2014.05.003.
- [22] M. Akhtaruzzaman, S. C. Barman, M. A. Hossain, M. Ahmad, and R. A. Ali, "Cloud enabled AI smart energy infrastructure for industrial and utility applications," in *2025 8th Int. Conf. Energy Conserv. Efficiency (ICECE)*, Lahore, Pakistan, 2025, pp. 1–6, doi: 10.1109/ICECE69114.2025.11272935.
- [23] Y. Liu *et al.*, "Study on the surface quality of overhanging holes fabricated by additive/subtractive hybrid manufacturing for Ti6Al4V alloy," *Metals*, vol. 14, no. 9, p. 979, 2024, doi: 10.3390/met14090979.
- [24] A. Loyda, M. Arizmendi, S. Ruiz de Galarreta, N. Rodriguez-Florez, and A. Jimenez, "Meeting high precision requirements of additively manufactured components through hybrid manufacturing," *CIRP J. Manuf. Sci. Technol.*, vol. 40, pp. 199–212, 2023, doi: 10.1016/j.cirpj.2022.11.011.
- [25] Y. Mahale, S. Kolhar, and A. S. More, "Enhancing predictive maintenance in automotive industry: Addressing class imbalance using advanced machine learning techniques," *Discov. Appl. Sci.*, vol. 7, no. 3, p. 340, 2025, doi: 10.1007/s42452-025-06827-3.
- [26] A. Mechete, F. Tarlochan, and M. Kucukvar, "A review of conventional versus additive manufacturing for metals: Life-cycle environmental and economic analysis," *Sustainability*, vol. 15, no. 16, p. 12299, 2023, doi: 10.3390/su151612299.
- [27] M. Merklein, D. Junker, A. Schaub, and F. Neubauer, "Hybrid additive manufacturing technologies-An analysis regarding potentials and applications," *Phys. Procedia*, vol. 83, pp. 549–559, 2016, doi: 10.1016/j.phpro.2016.08.057.
- [28] H. Nagamatsu, H. Sasahara, Y. Mitsutake, and T. Hamamoto, "Development of a cooperative system for wire and arc additive manufacturing and machining," *Addit. Manuf.*, vol. 31, p. 100896, 2020, doi: 10.1016/j.addma.2019.100896.
- [29] B. Nau, A. Roderburg, and F. Klocke, "Ramp-up of hybrid manufacturing technologies," *CIRP J. Manuf. Sci. Technol.*, vol. 4, no. 3, pp. 313–316, 2011, doi: 10.1016/j.cirpj.2011.04.003.
- [30] G. Neumann *et al.*, "A data-based certification approach for additively manufactured metal aircraft components," *Prog. Addit. Manuf.*, vol. 10, pp. 4061–4071, 2025, doi: 10.1007/s40964-025-01107-3.
- [31] M. A. Hossain and M. A. A. Bhuiyan, "Digital twin-based process optimization and defect prediction in metal additive manufacturing for critical mechanical components," *Brit. J. Multidiscip. Stud.*, vol. 3, no. 2, pp. 57–72, 2025, doi: 10.32996/bjmss.2025.3.2.5.
- [32] K. Osipovich *et al.*, "Wire-feed electron beam additive manufacturing: A review," *Metals*, vol. 13, no. 2, p. 279, 2023, doi: 10.3390/met13020279.
- [33] J. P. M. Pragana, R. F. V. Sampaio, I. M. F. Bragança, C. M. A. Silva, and P. A. F. Martins, "Hybrid metal additive manufacturing: A state-of-the-art review," *Adv. Ind. Manuf. Eng.*, vol. 2, p. 100032, 2021, doi: 10.1016/j.aime.2021.100032.
- [34] G. Prasad *et al.*, "Advancing sustainable practices in additive manufacturing: A comprehensive review on material waste recyclability," *Sustainability*, vol. 16, no. 23, p. 10246, 2024, doi: 10.3390/su162310246.

- [35] B. A. Praveena *et al.*, "A comprehensive review of emerging additive manufacturing (3D printing technology): Methods, materials, applications, challenges, trends and future potential," *Mater. Today Proc.*, vol. 52, pp. 1309–1313, 2022, doi: 10.1016/j.matpr.2021.11.059.
- [36] M. Á. Rabalo, A. García, and E. M. Rubio, "Emerging trends in hybrid additive and subtractive manufacturing," *Appl. Sci.*, vol. 15, no. 11, p. 6102, 2025, doi: 10.3390/app15116102.
- [37] U. Rokkala *et al.*, "Advancements and applications of wire arc additive manufacturing with future perspectives," in *Engineering Advanced Materials for Manufacturing, Energy, and Smart Systems*, D. Balakrishnan, R. Buradagunta, and W. Fernando, Eds., Hershey, PA, USA: IGI Global Scientific Publishing, 2026, pp. 195–212, doi: 10.4018/979-8-3373-9454-1.ch006.
- [38] M. A. Hossain, "Residual stress mitigation and distortion control in laser powder bed fusion components for high-reliability engineering applications," *Amer. J. Adv. Tech. Eng. Sol.*, vol. 1, no. 2, pp. 173–215, 2025, doi: 10.63125/1b3nyj37.
- [39] K. K. Saxena, M. Bellotti, J. Qian, D. Reynaerts, B. Lauwers, and X. Luo, "Chapter 2 - Overview of hybrid machining processes," in *Hybrid Machining*, London, UK: Academic Press, 2018, pp. 21–41, doi: 10.1016/B978-0-12-813059-9.00002-6.
- [40] G. Schuh, J. Kreysa, and S. Orilski, "Roadmap 'Hybride Produktion'," *Z. Wirtsch. Fabr.*, vol. 104, no. 5, pp. 385–391, 2009, doi: 10.3139/104.110072.
- [41] N. P. V. Sebbe, F. Fernandes, V. F. C. Sousa, and F. J. G. Silva, "Hybrid manufacturing processes used in the production of complex parts: A comprehensive review," *Metals*, vol. 12, no. 11, p. 1874, 2022, doi: 10.3390/met12111874.
- [42] L. Segovia-Guerrero, N. Baladés, J. J. Gallardo-Galán, A. J. Gil-Mena, and D. L. Sale, "Additive vs. subtractive manufacturing: A comparative life cycle and cost analyses of steel mill spare parts," *J. Manuf. Mater. Process.*, vol. 9, no. 4, p. 138, 2025, doi: 10.3390/jmmp9040138.
- [43] A. N. Soe *et al.*, "Effect of post-processing treatments on surface roughness and mechanical properties of laser powder bed fusion of Ti-6Al-4V," *J. Mater. Res. Technol.*, vol. 32, pp. 3788–3803, 2024, doi: 10.1016/j.jmrt.2024.08.197.
- [44] D. Sommer, B. Götzendorfer, C. Esen, and R. Hellmann, "Design rules for hybrid additive manufacturing combining selective laser melting and micromilling," *Materials*, vol. 14, no. 19, p. 5753, 2021, doi: 10.3390/ma14195753.
- [45] P. Stahmann, M. Nebel, and C. Janiesch, "AI-based real-time anomaly detection in industrial engineering: A structured literature review, taxonomy, and research agenda," *Comput. Ind. Eng.*, vol. 207, p. 111236, 2025, doi: 10.1016/j.cie.2025.111236.
- [46] G. F. Sun *et al.*, "Laser metal deposition as repair technology for 316L stainless steel: Influence of feeding powder compositions on microstructure and mechanical properties," *Opt. Laser Technol.*, vol. 109, pp. 71–83, 2019, doi: 10.1016/j.optlastec.2018.07.051.
- [47] D. Svetlizky *et al.*, "Directed energy deposition (DED) additive manufacturing: Physical characteristics, defects, challenges and applications," *Mater. Today*, vol. 49, pp. 271–295, 2021, doi: 10.1016/j.mattod.2021.03.020.
- [48] R. Tosi, E. Muzangaza, X. P. Tan, D. Wimpenny, and M. M. Attallah, "Hybrid electron beam powder bed fusion additive manufacturing of Ti-6Al-4V: Processing, microstructure, and mechanical properties," *Metall. Mater. Trans. A*, vol. 53, no. 3, pp. 927–941, 2022, doi: 10.1007/s11661-021-06565-2.